

Contemporary Insulation

Type of insulation	Application	Approx R per inch	Description
Fiberglass loose-fill	Attic Ceilings	~R-2.5	Short fibrous and fluffy texture, white color, itchy to touch, formaldehyde free
Fiberglass batts (unfaced/paper faced/foil faced)	Wall Cavities	~R-3.7	Long fibrous and fluffy texture, white or pink color, itchy to touch
Fiberglass wall spray (glue application)	Wall Cavities	~R-3.7	Short fibrous and fluffy texture, white color, itchy to touch, formaldehyde free
Cellulose loose-fill	Attic Ceilings	~R-3.7	Shredded paper texture, light brown color, non-itch
Cellulose wall spray (water application)	Wall Cavities	~R-3.7	Shredded paper texture, light brown color, non-itch
Semi-rigid open cell urethane spray foam (0.5 lb density)	Roofline & Walls	~R-3.8	Semi-ridged sponge texture, off white color, non-itch
Semi-rigid open cell urethane pour in place foam (0.5 lb density)	Wall Cavities	~R-3.8	Semi-ridged sponge texture, off white color, non-itch
Rigid closed cell urethane spray foam (2.0 lb density)	Roofline & Walls	~R-5.5	Ridged Styrofoam like texture, off white color, non-itch